

19



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



11 Publication number:

**0 256 453 B1**

12

## EUROPEAN PATENT SPECIFICATION

45 Date of publication of patent specification: **27.05.92** 51 Int. Cl.<sup>5</sup>: **G21G 4/08**

21 Application number: **87111468.2**

22 Date of filing: **07.08.87**

54 Dispensing device for radionuclide generators.

30 Priority: **11.08.86 DE 8621529 U**

43 Date of publication of application:  
**24.02.88 Bulletin 88/08**

45 Publication of the grant of the patent:  
**27.05.92 Bulletin 92/22**

84 Designated Contracting States:  
**AT BE CH DE ES FR GB GR IT LI LU NL SE**

56 References cited:  
**US-A- 3 774 036**  
**US-A- 3 848 773**  
**US-A- 4 192 438**

73 Proprietor: **E.R. Squibb & Sons, Inc.**  
**Lawrenceville-Princeton Road**  
**Princeton, N.J. 08540-4000(US)**

72 Inventor: **Klatte, Bernd**  
**Westendstrasse 1**  
**W-8400 Regensburg(DE)**  
Inventor: **Ferre, Vincenzo**  
**Erlenstrasse 3**  
**W-8411 Waldetzbach(DE)**  
Inventor: **Herrmann, Fritz**  
**Dietrich Bonhoefferstrasse 41**  
**W-6054 Rotgau 6(DE)**  
Inventor: **Hebborn, Hans-Gerd**  
**Bergstrasse 19**  
**W-8405 Donaustauf(DE)**  
Inventor: **Poliwczyk, Oskana**  
**Galgenbergstrasse 8**  
**W-8400 Regensburg(DE)**

74 Representative: **Vossius & Partner**  
**Siebertstrasse 4 P.O. Box 86 07 67**  
**W-8000 München 86(DE)**

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

## Description

The invention refers to a dispensing device, in particular for radionuclide generators.

Nuclide generators are used for producing radionuclides. They are essentially composed of a generator column on the matrix of which a longer-lived initial stage of the desired radionuclide, the so-called parent nuclide, is fixed, of an eluant container, and of an eluate container. The single components are connected to each other via hollow needles. The short-lived radionuclide, the so-called daughter nuclide, is produced by the elution of the mother nuclide.

In the nuclide generator disclosed in DE-U-77 08 973, the eluate, which can be a physiological salt solution, in the eluant container, is suctioned through the generator column by means of the evacuated eluate container. Thus the amount of eluate obtained corresponds to the vacuum which prevails in the eluate container at the beginning of the process. The disadvantage of this arrangement is that it is not possible to exactly dispense the amount of eluate obtained.

DE-A-22 36 565 discloses a device composed of a generator column, transporting means, an eluant container and an eluate container. This device enables arbitrary transportation of any amount of eluate into the eluate container. In doing so, transport means - for example a hose pump whose pumping capacity, i.e. the amount of liquid per time unit, is known - are operated for a certain period of time according to the desired yield of eluate. The transport means and its control means necessary for this purpose are highly complex and thus expensive, especially when used for precise measuring.

US-A-3,774,035 describes a dispensing apparatus for radionuclide generators according to the preamble of claim 1. US-A-3,848,773 describes a device for dispensing a pre-measured amount of radioactive gas by shifting a needle relative to the sealed vial.

In contrast to the prior art, the present invention is based on the object of providing a simple dispensing system by means of which in particular the elution of a radionuclide generator column with variable, arbitrarily choosable volumes of the fluid is possible.

This object is solved by the features of the claimed invention.

The invention is based on the idea of limiting the amount of eluant available for the elution. It is thereby possible to precisely adjust the yield of eluate, in particular in a radionuclide generator in which elution is performed via a small, evacuated collecting bottle, i.e. the eluate container.

According to a preferred embodiment of the

invention, the device comprises a suction needle and an aeration needle arranged parallel thereto which both project into the eluant container. The eluant is suctioned through the generator column via the suction needle for instance by a vacuum prevailing in the eluate container. The amount of air or protective gas which corresponds to the suctioned amount of eluant is supplied to the eluant container via the aeration needle.

According to the preferred embodiment of the invention, the shifting device comprises a support and a slide element which is shiftably arranged thereto. While the slide element is attached to the receptacle, the support is firmly connected to the fixing device for the needles.

In an advantageous embodiment of the invention the eluant container is a small septum bottle with an opening occluded by a pierceable stopper made of elastic material. Thus, it is possible to advantageously pierce the stopper with the suction needle or the aeration needle through the stopper without the danger of any liquid leaking out. It is thus possible to arrange the small septum bottle so that its opening points downwards.

According to a specific embodiment of the invention, the receptacle for the eluant container is a hollow cylinder having approximately the same length as the small septum bottle and whose cylindrical interior space is essentially adapted to the external dimension of the small septum bottle. The preferred embodiment thereof is that the small septum bottle is arranged in the receptacle in such a way that it maintains its position during operation.

The receptacle advantageously comprises an exterior casing, said casing serving as a slide element. This casing may be a sliding material, for instance rubber.

According to a further embodiment of the invention, the support is integrally connected to a base plate and has the essential form of a hollow cylinder whose dimensions are chosen in such a way that the receptacle is shiftable within the support. A screw connection or a slide-blocking casing of the receptacle or a lining of the cylindrical support has the advantage that the receptacle can be shifted into any position within the support. In order to secure the relative position of the container and the support, a fixing screw may be provided in the support, said fixing screw being screwable radially and inwards and pressing against the receptacle or the container.

According to the invention, the base plate comprises a recess near the cylinder axis of the support, which recess receives the fixing device.

Hereinafter the invention is explained in more detail by means of the Figures.

FIG. 1 shows an embodiment of the dispensing device according to the invention, the elution vol-

ume being minimal.

FIG. 2 shows the dispensing device according to Fig. 1, the elution volume being in the medium range.

FIG. 3 shows the dispensing device according to Fig. 1, the elution volume being maximal.

The embodiment of the invention shown in the Figures comprises a small septum bottle 1 in a hollow-cylindrical receptacle 7, the opening 12 of which points downwards. The opening 12 of the small septum bottle 1 is occluded with a stopper 13 made of pierceable, elastic material. A suction needle 4 and, if necessary, an aeration needle 6 project through the stopper 13 essentially parallel to the longitudinal axis 5 of the small septum bottle or the hollow-cylindrical receptacle 7. The needles 4 and 6 may be fixed at the base plate 14 by means of a fixing device 8, their tips 3 and 2 pointing upwards. This can for instance be done by means of a stopper-like disk which is made of elastic material and inserted into the aperture of the base plate, the needles 4 and/or 6 being pierced through the disk 8. As an alternative the needles may be fixed to the disk by means of an adhesive; in this case the disk need not be made of a pierceable material, but should be provided with holes for receiving the needles. As a third alternative the holes of the disk may be provided with internal threads and the needles should at least partially be provided with an external thread so that the needles can be screwed into the holes of the disk.

A hollow-cylindrical support 10 is concentrically arranged around the fixing device 8. The internal dimensions of said support essentially correspond to the external dimensions of the receptacle. The receptacle is arbitrarily shiftable within the support in frictional connection or in form closure and is fixable in any position by means of a cooperating internal and external thread at the support 10 and the receptacle 7 or a slide-blocking casing 9 which coats the external surface of the receptacle 7, or a fixing screw 17 screwable into the support casing. As can be taken from Figures 1 to 3, the receptacle 7 and thus the small septum bottle 1 is arbitrarily adjustable between a lower end position (Fig. 1) and an upper end position (Fig. 3). When the adjustment is performed in the direction of the longitudinal axis of the needles, the tips 3, 2 of the needles 4, 6, respectively, project either to the bottom 11 of the small septum bottle 1 or only approximately to the opening 12 of the small septum bottle 1. Thus the piercing depth of the suction needle and the aeration needle 4, 6 into the small septum bottle is arbitrarily variable by means of this dispensing device. Since it is only possible to suction the solution over the tip of the needle, the volume of the eluant can be advantageously

changed by altering the piercing depth.

The piercing depth and the volume to be eluted are just about reciprocally proportional to each other (if the cross-section of the small septum bottle is constant), as illustrated by the schematic Figures. When the piercing depth is great, only a small volume is suctioned via the suction needle 4 and generator column (not shown) as well as the needle 16 into a small, evacuated collecting bottle 15 (Fig. 1). If the dispensing device is fixed at a medium piercing depth, a correspondingly greater volume of the fluid is suctioned off (Fig. 2). The maximum elution volume is achieved at the minimum piercing depth (Fig. 3).

The device according to the present invention has the advantage that only a specific amount of eluant is flushed through the generator column (not shown) between the small septum bottle and the small collecting bottle independent of the vacuum prevailing in the small, evacuated bottle 15 at the beginning of the process of elution. Preferably the amount of eluant is to be exactly adjusted by means of a scale provided at the receptacle.

Apart from the described embodiment of the invention it is also possible to rigidly secure the small collecting bottle and to adjust the needles in their height, instead, so that the piercing depth can be varied. It is also possible to arrange the eluant container in an upright fashion, i.e. the opening of the container points upwards and the needles project into the eluant container from the top to the bottom.

Although the invention has been described in detail in connection with an eluant container for radionuclide generators, it is also possible to use the invention in any kind of dispensed evacuable containers in addition to this preferred application.

## Claims

1. A dispensing apparatus for radionuclide generators comprising:
  - a) an eluant container (1);
  - b) at least one hollow needle (4, 6) sealingly and shiftably attached to the container (1), a tip of said needle projecting into said container (1); and
  - c) means for arbitrarily fixing and shifting the at least one needle (4, 6) relative to the container (1) whereby the projection of the tip of the at least one needle into the container (1) can be changed;
  - d) a receptacle (7) adapted to the form of said container (1) and disposed to receive said container (1); and
  - e) a fixing device (8) which holds the at least one needle (4, 6) at a distance from its tip (3; 2);

characterized by

f) shifting means (9, 10) for allowing the fixing device (8) and receptacle (7) to be moved relative to each other along the longitudinal axis of the at least one needle between an upper and lower end position such that the tip of the at least one needle projects into the container (1) approximately to the bottom of the container in the lower end position and approximately to the opposite end of the container in the upper end position.

2. The apparatus of Claim 1 wherein said at least one needle further comprises a suction needle (4) and an aeration needle (6). 15
3. The apparatus of Claim 1 or 2 wherein said shifting means further comprises:
  - a support (10) for the receptacle (7); and 20
  - a slide element (9) shiftably arranged with respect to the support and attached to the receptacle (7).
4. The apparatus of any of Claims 1 to 3 wherein said container comprises a small septum bottle (1) having a pierceable stopper (13) of elastic material which occludes a small opening (12) of the bottle (1). 25
5. The apparatus of Claim 4 wherein said receptacle (7) comprises a hollow cylinder having approximately the same length as the small septum bottle (1) and whose cylindrical interior space is adapted to the external dimension of the small septum bottle (1). 30
6. The apparatus of Claim 5 wherein said slide element (9) comprises a casing at the exterior of said hollow cylinder. 35
7. The apparatus of Claim 6 wherein said apparatus further comprises a base plate (14) and said support is integrally connected to said base plate (14), said support comprising a second hollow cylinder whose length approximately corresponds to the length of the receptacle (7) and whose internal cross-section approximately corresponds to the external cross-section of the casing (9) of the receptacle (7). 40
8. The apparatus of Claim 7 wherein the receptacle (7) is shiftably disposed within the support (10). 45
9. The apparatus of Claim 7 or 8 wherein the base plate (14) comprises a recess near the cylindrical axis of the support (10), which 50

recess receives the fixing device (8).

## Revendications

- 5 1. Appareil distributeur pour générateurs de radionucléides, comprenant :
  - a) un récipient à éluant (1) ;
  - b) au moins une aiguille creuse (4, 6) fixée de manière étanche et déplaçable au récipient (1), une pointe de ladite aiguille faisant saillie dans ledit récipient (1) ; et 10
  - c) un moyen permettant de fixer arbitrairement et de déplacer au moins une aiguille (4, 6) par rapport au récipient (1) de manière à pouvoir modifier la longueur d'enfoncement de la pointe d'au moins une aiguille dans le récipient (1) ;
  - d) un réceptacle (7) adapté à la forme dudit récipient (1) et disposé de façon à recevoir ledit récipient (1) ; et
  - e) un dispositif de fixation (8) qui maintient au moins une aiguille (4, 6) à une certaine distance de sa pointe (3 ; 2); 15
  - caractérisé par
  - f) un moyen de déplacement (9, 10) permettant au dispositif de fixation (8) et au réceptacle (7) de se déplacer l'un par rapport à l'autre le long de l'axe longitudinal d'au moins une aiguille, entre une position extrême haute et une position extrême basse telles que la pointe d'au moins une aiguille fait saillie dans le récipient (1) à peu près jusqu'au fond du récipient dans la position extrême basse et à peu près jusqu'à l'extrémité opposée du récipient dans la position extrême haute. 20
2. Appareil selon la revendication 1, dans lequel au moins une aiguille comprend en outre une aiguille d'aspiration (4) et une aiguille d'aération (6). 25
3. Appareil selon la revendication 1 ou 2, dans lequel ledit moyen de déplacement comprend en outre :
  - un support (10) pour le réceptacle (7) ; et
  - un élément coulissant (9) disposé de façon à pouvoir se déplacer par rapport au support et fixé au réceptacle (7). 30
4. Appareil selon l'une quelconque des revendications 1 à 3, dans lequel ledit récipient comprend une petite bouteille à diaphragme (1) comportant un bouchon transperçable (13) en matériau élastique qui bouche une petite ouverture (12) de la bouteille (1). 35
5. Appareil selon la revendication 4, dans lequel 40

ledit réceptacle (7) comprend un cylindre creux ayant à peu près la même longueur que la petite bouteille à diaphragme (1), et dont l'espace intérieur cylindrique est adapté à la dimension externe de la petite bouteille à diaphragme (1).

6. Appareil selon la revendication 5, dans lequel ledit élément coulissant (9) comprend un boîtier à l'extérieur dudit cylindre creux.
7. Appareil selon la revendication 6, comprenant en outre une plaque de base (14) et dans lequel ledit support fait corps avec ladite plaque de base (14), ledit support comprenant un second cylindre creux dont la longueur correspond à peu près à la longueur du réceptacle (7) et dont la section droite interne correspond à peu près à la section droite externe du boîtier (9) du réceptacle (7).
8. Appareil selon la revendication 7, dans lequel le réceptacle (7) est disposé de façon à pouvoir se déplacer à l'intérieur du support (10).
9. Appareil selon la revendication 7 ou 8, dans lequel la plaque de base (14) comprend un évidement à proximité de l'axe cylindrique du support (10), évidement qui reçoit le dispositif de fixation (8).

#### Patentansprüche

1. Abgabevorrichtung für Radionuklidgeneratoren mit:
  - a) einem Elutionsmittelbehälter (1);
  - b) wenigstens einer mit ihrer Spitze in den Behälter (1) hineinragenden Kanüle (4, 6), die dicht und verschiebbar an dem Behälter (1) befestigt ist; und
  - c) einer Einrichtung zum beliebigen Fixieren und Verschieben der wenigstens einen Kanüle (4, 6) relativ zu dem Behälter (1), wobei das Hineinragen der Spitze der wenigstens einen Kanüle in den Behälter (1) verändert werden kann;
  - d) einer Aufnahmeeinrichtung (7), die der Form des Behälters (1) angepaßt und zur Aufnahme des Behälters (1) angeordnet ist; und
  - e) einer Halteeinrichtung (8), die die wenigstens eine Kanüle (4, 6) an einer von deren Spitze (3; 2) beabstandeten Stelle festhält;


**gekennzeichnet durch**

  - f) eine Verstelleinrichtung (9, 10), mit der die Aufnahmeeinrichtung (7) und die Halteeinrichtung (8) relativ zueinander längs der Längsachse der wenigstens einen Kanüle

zwischen einer oberen und unteren Endposition so bewegt werden kann, daß die Spitze der wenigstens einen Kanüle in den Behälter (1) ragt, und zwar in der unteren Endstellung bis etwa zum Boden des Behälters und in der oberen Endstellung bis etwa zum anderen Ende des Behälters (1).

2. Vorrichtung nach Anspruch 1, wobei die wenigstens eine Kanüle ferner eine Ansaugkanüle (4) und eine Belüftungskanüle (6) aufweist.
3. Vorrichtung nach Anspruch 1 oder 2, wobei die Verstelleinrichtung ferner aufweist: einen Ständer (10) für die Aufnahmeeinrichtung (7) und ein Stellelement (9), das gegen den Ständer verschiebbar angeordnet und an der Aufnahmeeinrichtung (7) befestigt ist.
4. Vorrichtung nach einem der Ansprüche 1 bis 3, wobei der Behälter ein Septumfläschchen (1) mit einem durchstechbaren Stöpsel (13) aus elastischem Material, das eine kleine Öffnung (12) des Fläschchens (1) verschließt, aufweist.
5. Vorrichtung nach Anspruch 4, wobei die Aufnahmeeinrichtung im wesentlichen ein Hohlzylinder mit etwa der gleichen Länge wie das Septumfläschchen (1) ist und dessen zylindrischer Innenraum den Außenabmessungen des Septumfläschchens (1) angepaßt ist.
6. Vorrichtung nach Anspruch 5, wobei das Stellelement (9) ein Gehäuse an der Außenseite des Hohlzylinders aufweist.
7. Vorrichtung nach Anspruch 6, wobei ferner eine Grundplatte (14) vorgesehen ist und der Ständer einstückig mit der Grundplatte (14) verbunden ist, wobei der Ständer einen zweiten Hohlzylinder aufweist, dessen Länge etwa der Länge der Aufnahmeeinrichtung (7) und dessen Innenquerschnitt etwa dem Außenquerschnitt der Ummantelung (9) der Aufnahmeeinrichtung (7) entspricht.
8. Vorrichtung nach Anspruch 7, wobei die Aufnahmeeinrichtung (7) innerhalb des Ständers (10) verschiebbar angeordnet ist.
9. Vorrichtung nach Anspruch 7 oder 8, wobei die Grundplatte (14) etwa im Bereich der Zylinderachse des Ständers (10) eine Ausnehmung aufweist, die die Halteeinrichtung (8) aufnimmt.

Fig. 1






Fig. 3




Fig. 2